

303 FarmPRO F-2



303 FarmPRO is an aesthetically improved modern F2 design. It has an optimized rib design suitable for both on and off road applications. The specially designed rib angles and radius ensure better roadability. Additional rubber layer under tread provides penetration resistance and improved sidewall deflection ensures better stability.



Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR	Load index speed Sym	Infl. press.	Recommend load, kg (lbs)						
		SW	OD						Speed, km/h (mph)						
		mm in	mm in						10 ⁽¹²⁾ 6	15 9	20 12	25 16	30 19	35 22	40 25
5.00-15	4.00E	140	665	309.7	1995	4	2.8	550	-	490	420	365	-	-	-
		5.5	26.2	12.2	78.5	73A6/65A8	41	1210	-	1080	930	810	-	-	-
5.50-16	4.00E	150	710	337.35	2139	6	3.7	800	-	720	610	530	-	420	970
		5.9	28	13.3	84.2	86A6/78A8	54	1760	-	1590	1350	1170	-	930	2140
6.00-16	4.50E	165	735	348	2206	6	3.3	840	-	760	640	560	-	450	1060
		6.5	28.9	13.7	86.9	88A6/80A8	48	1850	-	1680	1410	1240	-	990	2330
	4.5E	165	735	348	2206	8	4.5	1010	-	900	770	670	-	540	420
		6.5	28.9	13.7	86.9	94A6/87A8	65	2230	-	1980	1700	1480	-	1190	930
6.50-16	4.00E	175	760	353.95	2254	6	3.1	920	-	830	710	615	-	490	450
		6.9	29.9	13.9	88.7	91A6/83A8	45	2030	-	1830	1570	1360	-	1080	990
7.50-16	5.50F	205	805	360	2440	6	2.8	1130	-	1010	860	750	-	600	540
		8.1	31.7	14.2	96.1	98A6/90A8	41	2490	-	2230	1900	1650	-	1320	1190
	5.5	205	805	373.25	2426	8	3.7	1310	-	1180	1010	875	-	700	490
		8.1	31.7	14.7	95.5	103A6/96A8	54	2890	-	2600	2230	1930	-	1540	1080
9.00-16	W8	210	815	382	2473	10	4.7	1545	1473	1391	1185	1030	927	824	824
		8.3	32.1	15	97.4	109A6/101A8	68	3410	3250	3070	2610	2270	2040	1820	1820
10.00-16	W8L	234	855	395	2585	10	3.9	1880	-	1690	1440	1250	-	1000	600
		9.2	33.7	15.6	101.8	116A6/108A8	57	4150	-	3730	3180	2760	-	2210	1320
11.00-16	W8L	275	895	410	2700	8	2.8	1820	-	1640	1400	1215	-	970	700
		10.8	35.2	16.1	106.3	115A6/107A8	41	4010	-	3620	3090	2680	-	2140	1540
7.50-18	5.50F	315	965	432.8	2839	8	2.4	1980	-	1780	1520	1320	-	1060	1000
		12.4	38	17.0	111.8	118A6/110A8	35	4370	-	3920	3350	2910	-	2340	2200
4.00-19	3.00D	205	860	395	2590	8	3.7	1460	-	1320	1120	975	-	780	780
		8.1	33.9	15.6	102	107A6/99A8	54	3220	-	2910	2470	2150	-	1720	1720
6.00-19	W8	112	716	330	2134	4	3.4	530	-	480	410	355	-	280	280
		4.4	28.2	13	84	72A6	49	1170	-	1060	900	780	-	620	620
7.50-20	5.5F	165	814	390	2485	6	3.3	980	-	880	750	650	-	520	520
		6.5	32	15.4	97.8	93A6	48	2160	-	1940	1650	1430	-	1150	1150
7.50-20	5.5F	205	905	425	2735	8	3.4	1550	-	1390	1180	1030	-	820	820
		8.1	35.6	16.7	107.7	109A6/101A8	49	3420	-	3060	2600	2270	-	1810	1810

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	Load index PR Sym	Infl. press.	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm in	mm in					Free Rolling						
7.50-16	5.5	210	815	382	2473	10	4.7	1545	1473	1391	1185	1030	927	824
		8.3	32.1	15	97.4	109A6/101A8	68	3410	3250	3070	2610	2270	2040	1820